



PRODUCT EASY INSTALL INSTRUCTIONS

Premier Series

Your Premier Bench has been designed for easy installation so that you can quickly begin enjoying all the benefits of your Ultimate Golf Seat(s)!

If you have seats that need to be removed, simply:

1. Remove the existing backs by removing the bolts. (See Picture 1)
2. Remove the existing seat by lifting it forward and up, which will release the hinge brackets from their position. It is strongly recommended using two people for this step. (See Picture 2)
3. Remove existing seat.

To install your Ultimate Golf Seats, simply:

1. Remove the eight bolts and sixteen washers from the separate packet. (See Picture 3)
2. Take each bolt, and first slide the flat washer, then second, slide the split lock washer onto the bolt. (See Picture 4)



Picture 3



Picture 4

3. Remove the seat from the packaging and set it front down on a padded, level surface. Locate the two L-shaped Back Supports and orient the short ends to the holes located on the bottom/rear of the seat using a 7/16" wrench or socket. (See Picture 5)
4. Set the seat right-side-up and using the remaining 4 bolts, with washers in place, secure the back onto the long end of the Back Support using a 7/16" wrench or socket. (See Picture 6)
5. With one person on each end of the seat, lift and place onto the cart by inserting the hinge brackets into their position and lowering the seat. (See Picture 7)



Picture 1



Picture 2



Picture 5



Picture 6



Picture 7